Philips
Coaxial cable

5 m
F-Type Black

SWV2845W

Ensure a reliable connection

with this satellite coaxial cable

Depend on this satellite coaxial cable for transferring audio/video signals between your components.

Enjoy good picture quality
- Crafted with quality construction
- Nickel-plated connectors for reliable contact

Enjoy good audio quality
- High purity copper conductor for reliable signal transfer

Easy installation
- Non-slip ergonomic grip for easy use

Enjoy extended durability
- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

Coaxial cable
5 m F-Type Black

SWV2845W/10

Specifications

Packaging dimensions
- Packaging dimensions (W x H x D): 19.6 x 23.6 x 5.6 cm
- Nett weight: 0.220 kg
- Gross weight: 0.280 kg
- Tare weight: 0.060 kg
- EAN: 87 12581 38106 6
- Number of products included: 1
- Packaging type: Blister

Outer Carton
- Outer carton (L x W x H): 64.8 x 26.7 x 26.7 cm
- Nett weight: 2.640 kg
- Gross weight: 4.600 kg
- Tare weight: 1.960 kg
- EAN: 87 12581 38108 0
- Number of consumer packagings: 12

Inner Carton
- Inner carton (L x W x H): 24.4 x 20.6 x 24.4 cm
- Nett weight: 0.880 kg
- Gross weight: 1.240 kg
- Tare weight: 0.360 kg
- EAN: 87 12581 38107 3
- Number of consumer packagings: 4

Product highlights

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Molded plug
Molded plugs ensure secure connections between components and offer extended durability.

Quality construction
Quality construction uses only top grade materials to create products of extended durability.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Nickel-plated connectors
Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Issue date 2008-10-28
Version: 1.1.7
12 NC: 8670 000 35492
EAN: 87 12581 38106 6

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com